

BE9200/9400 Multi-Channel SD+ Encoders

The Telairity 2-channel BE9200 and 4-channel BE9400 are scalable, fully programmable broadcast quality encoders for standard definition and mobile video formats. Telairity's uniquely powerful hardware and software technology generates leading-edge video compression (H.264 or AVS) to achieve industry-leading video quality at very low bit rates for maximum transmission/storage efficiency. The 1RU BE9400 high density encoding platform also minimizes rack space to further reduce per-channel costs. Like all Telairity encoders, the BE9400 can be readily upgraded via a software download to add new features or enhance performance.



Features and Options

Video Encoding Features

- 4 fully independent channels with I/O configurable per channel pair (1 & 2, 3 & 4)
- ASI, SDI, or GigE IP input for pre-encoded content; separate SDI and optional Composite input for uncompressed content; uncompressed SDI source loop-out for monitoring, redirection
- Image Enhancement (Deringing, Deblocking, Flicker reduction, Deinterlacing) for maximum transcoded picture quality
- Input Formats: 576i (PAL), 480i (NTSC)
- Input Codecs: MPEG-4 H.264/AVC to L4 • MPEG-4-ASP L5 • MPEG-2 Main Profile Main & High Levels • MPEG-1 • VC1 Advanced Profile Level 3 • DivX 3.11/4/5/6 • DV • JPEG
- Two outputs per channel: choice of 2 ASI, 2 IP, or 1 each
- Output Codecs: H.264/AVC High, Main, Baseline Profiles; AVS-P2
- Supports all standard output resolutions, including: D1, 4CIF, VGA, HVGA, WQVGA, CIF, QVGA, HQVGA, QCIF, QQVGA (SQVGA), SQCIF, etc.
- Reduced frame rates: 1/3, 1/2, 2/3 of 30fps
- Customizable frame sizes and rates available at no additional cost
- Rate Control – 5.0 to 0.1 Mbps; Constant or Variable Bit Rate (CBR, VBR)
- GOP mode: selectable fixed length or adaptive
- Enhanced scene change detection; CAVLC or CABAC entropy encoding
- Adjustable Spatial Preprocessing and Deblocking (Loop) Filters

Audio Encoding Features (per channel)

- SDI embedded audio input per SMP2 272M
 - Four programs (stereo pairs) per channel: Stereo, Dual Mono, Mono
- MPEG-1 Layer 2 encoding, bit rates: 64 to 384 Kbps
 - MPEG-4 AAC-LC & -HEv2 for better quality or lower bit rates (to 12 kbps)
- Dolby Digital / AC-3 and Dolby E pass-through

Control Features

- Web browser control via Ethernet interface
- Telairity Encoder and Network Management System applications
- Simple integration with standard SNMP systems

BE9400 MultiChannel SD/Mobile Encoder

Applications

The Telairity BE9200 and BE9400 multichannel SD & Mobile encoding platforms offer state of the art video compression for all SD and mobile television formats in a cost-effective, 1 RU form factor. They excel at low bit rates, and are targeted to IPTV, ITV, mobile and other applications where the lowest bit rates are needed and multiple channels must be accommodated.

Benefits

Space-saving compact 1RU design

Handles up to 4 independent SD/mobile channels, with up to 4 stereo audio programs per video channel

Based on the fully programmable Telairity-1 video architecture; full software upgradeability for easy maintenance and improvements.

Industry-leading video quality at ultra-low bitrates for SD and Mobile formats

MPEG-4 AAC-LC or -HE option for high audio quality at very low compressed bit rates; Dolby Digital (AC-3) and Dolby E pass-through also supported

"Instant on" startup and restart times

Non-stop design with dual redundant power supplies.

Options

Breakout cables for external audio inputs (digital and analog);

Composite input

Transcoding (MPEG-2, etc.)

G.703/E3 or DS3 output

Other Models

BE9110 Single channel with front panel control

BE9300 3 channel multi-format model (1 HD, 2 SD+)

Ordering Information

Part Numbers:

BE9200, BE9400

Contents

- BE9000-series Encoding Platform
- Power Cable: IEC to USA plug; optional Euro plug
- USB flash drive with backup copy of encoder firmware and manual

Requirements

- Web browser control system
- SDI input source video
 - SD SMPTE 259M
 - HD SMPTE 292M
- Input cables
 - 75 Ohm coaxial with BNC connector
 - Composite or component (SD)
- Output cables (either or both)
 - 75 Ohm coaxial with BNC connector
 - Cat5/6 Ethernet with RJ-45 connector

About Telairity

Telairity, based in Santa Clara, California designs, manufactures and markets H.264/AVC and other advanced encoding and transcoding solutions for broadcast and professional video applications. Telairity's breakthrough video architecture (Telairity-1™) is the foundation for all its real time encoding products, which combine outstanding video quality with state-of-the-art, video compression based on the AVC (H.264 / MPEG-4.10) standard to achieve the lowest possible bitrates.

Telairity

3375 Scott Blvd., Suite 300
 Santa Clara, CA 95054
 tel 408 764 0270
 fax 408 764 0271
 www.telairity.com

Network Compatibility

Inputs: Satellite, Cable, Terrestrial, IP; Digital or Analog
 Outputs: Streaming over 2.5G, 3G, 4G Cellular; 3GPP MBMS; DVB-H Mobile; MediaFLO; ATSC M/H; DSL, WiFi, WiMax broadband

Video Inputs

Input Format Options: 4 SD-SDI (SMPTE 259M) source inputs
 4 Composite analog source inputs (option)
 4 SDI, ASI or Gig-E transcoding inputs

Video Source Input Formats: 4:2:2 for 576i (PAL), 480i (NTSC)

Pre-encoded Input Formats: MPEG-4, MPEG-2, MPEG-1, VC-1, DivX, DV, JPEG

Frame Rates: 30, 29.97, 25, 24, 23.98 fps

Connectors: BNC for 75 ohm coax (SDI, ASI); Composite with RCA adaptor RJ-45 for Cat5/6 (Ethernet)

Audio Input

Input Format: Embedded in SDI per SMPTE 272M (SD)
 Dolby Digital (AC-3) and Dolby E pass-through
 External Audio: 2 digital AES + 2 analog L/R stereo pairs per channel

Compressed A/V Output

Output Interface: Digital Video Broadcast – Asynchronous Serial Interface (DVB-ASI), 270Mbps, buffered non-inverting
 10/100 Base-T Ethernet for IP

Packet Format: MPEG-2 188-byte Transport Stream (TS) packets in either TS/UDP/IP or TS/RTP/UDP/IP format with optional FEC

Compression Format: H.264 Profiles: High, Main, Baseline; AVS-P2

Compressed Bitrates: User programmable, CBR or VBR; 0.1 to 5.0 Mbps/channel

ASI Stream Out: Twist-lock BNC connectors (0, 1, 2 per channel)

IP Stream Out: RJ-45 connectors (0, 1, 2 per channel)

Control

Interface: 1 Ethernet control interface per channel pair with RJ-45 connector via hub (or switch) to Web browser controller

Control Application: Web browser Interface over Ethernet

Network Management: Telairity EMS/NMS or standard SNMP

Power Specifications

Input voltage: 100 to 240 VAC (Auto sensing); -48VDC option dual-redundant power supplies

Line frequency, Power: 47 to 63 Hz; 390 Watts maximum (4 channels)

Mechanical Specifications

Dimensions & Weight: 1RU (H) x 19" (W) x 28" (D) rack mountable, 25 lbs.

Environmental Specifications

Cooling: Forced air-cooling side to side

Operating Environment: -10° to 55°C; 5-95% humidity (non-condensing)



BE9400 Quad-Channel SD/Mobile Encoder Back Panel

Copyright 2012 by Telairity. All rights reserved. All products mentioned here are the trademarks or registered trademarks of their respective owners. Telairity reserves the right to make changes without notice and does not assume any liability arising from the application of this product.